Sub-Picosecond Injection of Electrons from Excited {Ru(2,2'-bipy-4,4'-dicarboxy)₂(SCN)₂} into TiO₂ Using Transient Mid-Infrared Spectroscopy

R.J. Ellingson, J.B. Asbury, S. Ferrere, H.N. Ghosh, J.R. Sprague, T. Lian, and A.J. Nozik

Presented at the 12th International Conference on Photochemical Conversion and Storage of Solar Energy Berlin, Germany August 9-14, 1998



1617 Cole Boulevard Golden, Colorado 80401-3393

NREL is a U.S. Department of Energy Laboratory
Operated by Midwest Research Institute • Battelle • Bechtel

Contract No. DE-AC36-98-GO10337

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or any agency thereof.

Available to DOE and DOE contractors from:
Office of Scientific and Technical Information (OSTI)
P.O. Box 62
Oak Ridge, TN 37831
Prices available by calling 423-576-8401

Available to the public from:

National Technical Information Service (NTIS)
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161
703-605-6000 or 800-553-6847
or
DOE Information Bridge
http://www.doe.gov/bridge/home.html



Sub-picosecond Injection of Electrons from Excited [Ru (2,2'-bipy-4,4'-dicarboxy)₂(SCN)₂] into TiO₂ Using Transient Mid-Infrared Spectroscopy *

Randy J. Ellingson, John B. Asbury ^a, Sue Ferrere, Hirendra N. Ghosh, ^a Julian R. Sprague, Tianquan Lian, ^a and Arthur J. Nozik

Center for Basic Sciences, National Renewable Energy Laboratory, Golden, Colorado, 80401, and ^aDepartment of Chemistry, Emory University, Atlanta, Georgia, 30322

Abstract

We have used femtosecond pump-probe spectroscopy to time resolve the injection of electrons into nanocrystalline TiO_2 film electrodes under ambient conditions following photoexcitation of the adsorbed dye, $[Ru(4,4'\text{-dicarboxy-}2,2'\text{-bipyridine})_2(NCS)_2]$ (N3). Pumping at one of the metal-to-ligand charge transfer absorption peaks and probing the absorption of electrons injected into the TiO_2 conduction band at 1.52 μ m and in the range of 4.1 to 7.0 μ m, we have directly observed the arrival of the injected electrons. Our measurements indicate an instrument-limited ~50-fs upper limit on the electron injection time under ambinet conditions in air. We have compared the infrared transient absorption for noninjecting (blank) systems consisting of N3 in ethanol and N3 adsorbed to films of nanocrystalline Al_2O_3 and ZrO_2 , and found no indication of electron injection at probe wavelengths in the mid-IR (4.1 to 7.0 μ m). At 1.52 μ m interferences exist in the observed transient absorption signal for the blanks.

Key words: dynamics of dye injection, N3, nanocrystalline TiO2

Introduction

Extensive efforts have been directed toward understanding the photoelectrochemical properties and charge transfer dynamics of dye-sensitized nanocrystalline semiconductor films. Such films used in photovoltaic cells have demonstrated highly efficient solar energy conversion (>10%) in recent years, 1-3. Dye-sensitized photoelectrochemical solar cells based on [Ru(4,4'dicarboxy-2,2'-bipyridine)2(NCS)2] (N3) adsorbed to nanocrystalline TiO2 rely on efficient charge-separation at the dye-TiO2 interface, and fast electron injection from the excited state of the adsorbed dye molecule into the TiO2 nanoparticle. Injection must be fast to compete with processes such as relaxation and degradation of the excited dye molecule. Several groups studying the transient absorption of the excited and oxidized states of the dye in the visible and near-IR, to determine the electron injection time in the N3-sensitized TiO2 (N3-TiO2) and similar systems, have reported evidence for ultrafast (≤1 ps) charge separation and electron injection 4-10. Tachibana et al. reported transient absorption measurements at 750 nm which were ascribed to the formation of oxidized N3 (pumped at 605 nm); analysis of the rise time of the 750 nm absorption indicated biphasic electron injection with injection times of 150 fs (instrument limited) and 1.2 ps.⁴ Hannappel et al.⁵ measured the rise of the near-infrared absorption of conduction band electrons at 1100 nm following photoexcitation of N3 at the lower-energy metal-to-ligand charge transfer (MLCT) absorption peak (550 nm); the near-infrared absorption signal was attributed to free or trapped electrons following injection. However, these authors believe that to obtain unambiguous results, it was necessary for these experiments to be conducted under ultra-high vacuum (UHV) conditions. These authors also challenged the assignment by Tachibana et al. of the 750 nm absorption band to oxidized N34; this challenge

has been answered in turn. 6,7 Heimer *et al.* 8 used a system with 30 ps resolution to time resolve the electron injection into $\mathrm{TiO_2}$ from the dye [Ru(4,4'-(COOCH_2CH_3)_2-2,2'-bipyridine)(2,2'-bypyridine)_2]⁺²; the instrument time response placed an upper limit on the injection time of ~20 ps. 10 Here we present further evidence, based on time-resolved infrared (TRIR) absorption measurements, for ultrafast electron injection times (50 fs \pm 25 fs) for the N3-TiO₂ electrode under ambient conditions. By probing the time-resolved mid-IR absorption produced by injected electrons, we are able to obtain unambiguous conclusions without the need for UHV. Probing in the mid-IR allows us to bypass the issue of the correct absorption spectrum for oxidized N3 and eliminate the possibility of any signal contributions from the cationic or excited states of the dye.

Materials and Methods

Titanium dioxide nanoparticle colloids were prepared as previously described, using Degussa P25 TiO₂ starting material. ¹² The Al₂O₃ nanoparticle colloid was prepared using a method similar to that used for TiO₂. The starting material for the alumina colloid was Degussa Aluminum Oxide C (primary particle size of 13 nm). The ZrO₂ colloid was prepared via hydrolysis of zirconium isopropoxide and heated at 220 °C using a procedure published previously for the preparation of colloidal TiO₂. Films were fired at 450 °C for 45 minutes in air. Films to be used with probe wavelengths longer than 5.5 μ m were prepared on 2.0-mm-thick CaF₂ substrates, both sides polished. Films to be used at wavelengths shorter than 5.5 μ m were prepared on either *c*-cut polished sapphire or fluorine-doped SnO₂ conducting glass substrates. TiO₂ and ZrO₂ films were 5 – 8 μ m thick with good transparency. Al₂O₃ films were ~15 μ m thick, and showed greater scattering than the TiO₂ films. Immersion and storage of the TiO₂, Al₂O₃, and ZrO₂ films in a room temperature ethanol solution containing 200 μ M N3 and 20 mM chenodeoxycholic acid ¹⁴ resulted in adsorption of the N3 dye to the porous film surface. The resulting dye-sensitized films showed an absorbance of ~1.0 at 400 nm and 550 nm. High purity N3 was purchased from Solaronix (Lausanne, Switzerland).

Pump-probe measurements were made using two different laser systems described previously 11.

Experimental Results

With the N3-TiO₂ sample exposed to air, transient absorption measurements using a visible pump and a visible or near-IR probe show a problematic long-lived absorption component. Hannappel *et al.* also observed such an accumulated signal for visible probe measurements made in a solvent environment;⁵ only when measuring solid state samples under UHV did the accumulated signal vanish. Our initial investigations of various samples pumped at 550 nm and probed at 1.52 μm showed long-lived signals as well as signals not attributable to absorption by injected electrons. Figure 1 shows data for N3-TiO₂, N3-ZrO₂, and N3-ethanol samples. The N3-TiO₂ sample shows an ultrafast rise of absorption and subsequent initial decay, similar to that reported by Hannappel *et al.*⁵ However, it is clear from measurements of the N3-ZrO₂, where significant injection is not expected, and N3-ethanol, where no semiconductor is present, that other sources of transient absorption at 1.52 μm are present from either N3* or N3 photoproducts in this near-IR region. To rule out nonlinear effects such as two photon (pump) absorption, we

have verified that the absorption signal is linear with pump pulse energy. The transient signal for $N3\text{-}TiO_2$ may very well be dominated by the injected electron absorption, but no clear conclusions can be drawn without well-behaved blanks to verify the absence of a signal arising from $N3^*$ or $N3^+$.

Due to a long-lived absorption we observed when probing at 1.52 μm, we made additional transient absorption measurements at longer IR-wavelengths. The samples were measured in air, and the linear absorbance at 2110 cm⁻¹ (4.74 µm) was 30 mO.D. for the N3-TiO₂ sample and 70 mO.D. for the N3-Al₂O₃ sample. Using the 1 kHz system, we used a pump pulse energy of 1.1 µJ at 400 nm and 100 fs pulsewidth to excite samples of N3-TiO2, N3-Al2O3, N3-ZrO₂, and unsensitized TiO₂. Probing the resultant absorption at 4.63 μm and 4.9 μm, we find no transient absorbance for either the $N3-Al_2O_3$ or $N3-ZrO_2$ samples, and only a small absorbance for the unsensitized TiO₂. N3-TiO₂ shows a transient absorbance maximum of ~3 mO.D. at 4.63 μm and ~6 mO.D. for 4.9 μm . Results are shown in Figure 2. The transient mid-IR signals can be well fit by a single exponential rise convoluted with the instrument response function. The best fits yield time constants of 50 fs \pm 25 fs, as shown by the solid lines in Fig. 2 (a) and (b). The risetime of 100 fs does not produce as satisfactory a fit of the data, as shown by the dashed line. The instrument response function was determined in a thin silicon wafer right before or after a kinetics scan at each wavelength. A typical response in silicon is shown in Fig. 2 (b); this signal can be well represented by the integration of a gaussian function with FWHM of 185 fs. The transient absorbance for the unsensitized TiO2 is ~0.6 mO.D., ~10% of the absorbance for N3-TiO2 at 4.9 µm. These results show conclusive and direct evidence of the arrival of electrons within the TiO2 following photoexcitation of adsorbed molecules of N3.

As shown in Figure 3, when probing at $6.6~\mu m$ we obtain similar results showing electron injection for N3-TiO₂, no injection for N3-Al₂O₃, and slight IR absorption for unsensitized TiO₂. In addition, the data shows a fast initial decay following the rise; this decay occurs on a ~50 fs timescale. The origin of the initial decay is not determined, but is consistent with either the cooling or trapping of the injected electrons. The free electron absorption cross-section is proportional to the density of states and relaxation of electrons toward the conduction band minimum is expected to result in reduced IR absorption. Trapping of electrons could also result in a reduced IR absorption. Our preliminary measurement of the spectral dependence of the IR absorption indicates an absorbance which increases with probe wavelength.

Discussion

Using TRIR absorption spectroscopy, we have measured the electron injection time for N3-TiO2. Pumping samples of N3-ethanol, N3-TiO2, N3-Al2O3, and N3-ZrO2 at 400 nm or 550 nm, we probed the absorption by injected electrons using infrared femtosecond pulses at 1.52 µm and also in the range of 4.1 to 7.0 µm. Our results from the 1.52 µm TRIR experiments show the presence of long-lived absorption, as well as absorption by N3-ethanol and N3-ZrO2. Any injection from N3-ZrO2 is likely quite inefficient, and N3-ethanol provides no free or trapped electrons; therefore, the absorption signals for these samples could be due to products of the photodegradation of N3 or possibly to lower-lying N3 excited state absorption. Hannappel *et al.*⁵ reported that measurements of the visible transient absorption made in a solvent or air environment exhibited an accumulated signal which they attributed to "side reactions". To overcome this spurious accumulated signal, they made all solid state measurements in a UHV environment. We have found that probing further into the IR, in the 4.1 to 7.0 µm range,

environment. We have found that probing further into the IR, in the 4.1 to 7.0 µm range, simplifies measurement of the TRIR absorption by injected electrons by eliminating the requirement of the UHV apparatus; we observed no accumulated or long-lived absorption components in this wavelength range. In addition, our results indicate that we eliminate the possibility of any contribution to the IR absorption signal arising from the dye excited or cationic states; the former could arise from non-injecting dye molecules. Analysis of our transient absorption data for probe wavelengths of 4.63, 4.9, and 6.6 μm , shows an instrument-limited electron injection time for N3-TiO₂ of \sim 50 fs. For Al₂O₃ with a bandgap of \sim 10 eV, and ZrO₂ with a bandgap of 5 eV, 15-18 the conduction band edge is expected to lie too far negative to allow injection from N3*. As expected, our TRIR absorption measurements indicate that while N3-TiO2 produces an IR-absorbing electron population within the semiconductor, no such absorption is present for the non-injecting N3-Al₂O₃ and N3-ZrO₂ samples. The broad IR absorption of N3-TiO2 could be due to free electrons, trapped electrons, or both. Data taken at $6.6 \mu m$ suggests a cooling or trapping of the injected electrons on the ~ 50 fs timescale. Efforts to measure the time-resolved injected-electron IR absorption spectrum for N3-TiO2 are underway.

Acknowledgement. R.J.E., S.F., J.R.S., and A.J.N. of NREL were supported by the U.S. Department of Energy, Office of Energy Research, Division of Chemical Sciences. J.A., H.N.G., and T.L. of EU were supported by the Petroleum Research Fund (administered by the American Chemical Society), the Emory University Research Committee, and the National Science Foundation CAREER award under grant No. 9733796. We thank Brian Fluegel for his assistance with the 1.52 μm transient absorption measurements.

References

- * The work reported here has been previously published in Ref. 11.
- (1) O'Regan, B.; Grätzel, M. Nature 1991, 353, 737.
- (2) Nazeeruddin, M. K.; Pechy, P.; Grätzel, M. Chem. Commun. 1997, 1705.
- (3) Grätzel, M. "Photoelectrochemical Solar Energy Conversion by Dye Sensitization," in *Future Generation Photovoltaic Technologies*, McConnell, R. D., Ed., A.I.P. Conf. Proc., 404, American Institute of Physics, Woodbury NY, 1997.
- (4) Tachibana, Y.; Moser, J. E.; Grätzel, M.; Klug, D. R.; Durrant, J. R. J. Phys. Chem. 1996, 100, 20056.
- (5) Hannappel, T.; Burfeindt, B.; Storck, W.; Willig, F. J. Phys. Chem. B 1997, 101, 6799.
- (6) Moser, J. E.; Noukakis, D.; Bach, U.; Tachibana, Y.; Klug, D. R.; Durrant, J. R.; Humphry-Baker, R.; Grätzel, M. J. Phys. Chem. B 1998, 102, 3649.
- (7) Hannappel, T.; Zimmermann, C.; Meissner, B.; Burfeindt, B.; Storck, W.; Willig, F. *J. Phys. Chem. B* **1998**, *102*, 3651.
 - (8) Heimer, T. A.; Heilweil, E. J. J. Phys. Chem. B 1997, 101, 10990.
 - (9) Ghosh, H. N.; Asbury, J. B.; Lian, T. J. Phys. Chem. B 1998, {in press}.
- (10) A more recent measurement with improved time resolution in the subpicosecond range revealed an injection time of ~500 fs (Heilweil, E.J., private communication).
 - (11) Ellingson, R.J.; Asbury, J.B.; Ferrere, S.; Ghosh, H.N.; Sprague, J.R.; Lian, T.; Nozik, A.J., J. Phys. Chem. B, 1998, 102, 6455.
 - (12) Nazeeruddin, M. K.; Kay, A.; Rodicio, I.; Humphry-Baker, R.; Müller, E.; Liska,

- P.; Vlachopoulos, N.; Grätzel, M. J. Am. Chem. Soc. 1993, 115, 6382.
 - (13) Zaban, A.; Ferrere, S.; Sprague, J.; Gregg, B. A. J. Phys. Chem. 1997, 101, 55.
 - (14) Kay, A.; Grätzel, M. J. Phys. Chem. 1993, 97, 6272.
 - (15) Bendoraitis, J. G.; Salomon, R. E. J. Phys. Chem. 1965, 69, 3666.
 - (16) Clechet, P.; Martin, J.; Oliver, R.; Vallouy, C. C. R. Acad. Sci. C 1976, 282, 887.
- (17) Kung, H. H.; Jarrett, H. S.; Sleight, A. W.; Ferretti, A. J. Appl. Phys. 1977, 48, 2463.
 - (18) Heimer, T. A.; Meyer, G. J. J. Lumin. 1996, 70, 468.

- Figure 1. TRIR absorption data for 550 nm pump and 1.52 μ m probe of N3-TiO2, N3-ZrO₂, and N3-ethanol (after Ref. 11)
- Figure 2. TRIR absorption data for probe wavelengths of (a) $4.63 \, \mu m$ and (b) $4.9 \, \mu m$ following photoexcitation by $400 \, nm$, $100 \, fs$ pulses. As seen in (a), neither N3- Al_2O_3 nor N3- ZrO_2 show evidence of injected electron absorption. The system response function from free-carrier absorption in silicon shown in (b) is seen to match very closely the rise of the absorption signal for N3- TiO_2 ; unsensitized TiO_2 shows a small absorption due to carriers photoexcited directly within the electrode. The rise times indicate an injection time ~ 50 fs (after Ref. 11)
- Figure 3. TRIR absorption of a 6.6 μ m probe for N3-TiO₂, N3-Al₂O₃, and unsensitized TiO₂ following photoexcitation by 400 nm, 100 fs pulses. The fast (~50 fs) rise of absorption for N3-TiO₂ is followed by an equally fast initial decay. The source of this decay has not been decisively assigned, though it is believed to be due to cooling or trapping of the injected electrons (after Ref. 11).





Figure 1.






Figure 2.

Figure 3.

REPORT DOCUMENTATION PAGE			Form Approved OMB NO. 0704-0188
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE May 1999	3. REPORT TYPE AND DATES COVERED Conference Paper	
4. TITLE AND SUBTITLE Sub-Picosecond Injection of Electrons from Excited [Ru (2,2'-bipy-4,4'-dicarboxy) ₂ (SCN) ₂] into TiO ₂ Using Transient Mid-Infrared Spectroscopy 6. AUTHOR(S) R.J. Ellingson, J.B. Asbury, S. Ferrere, H.N. Ghosh, J.R. Sprague, T. Lian, and A.J. Nozik			5. FUNDING NUMBERS C: TA: ER460040
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Renewable Energy Laboratory 1617 Cole Blvd. Golden, CO 80401-3393			8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER CP-590-25519
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY STATEMENT National Technical Information Service U.S. Department of Commerce 5285 Port Royal Road Springfield, VA 22161			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) We have used femtosecond pump-probe spectroscopy to time resolve the injection of electrons into nanocrystalline TiO ₂ film electodes under ambient conditions following photoexcitation of the adsorbed dye, [Ru(4,4'-dicarboxy-2,2'-bipyridine) ₂ (NCS) ₂] (N3). Pumping at one of the metal-to-ligand charge transfer adsorption peaks and probing the absorption of electrons injected into the TiO ₂ conduction band at 1.52 μm and in the range of 4.1 to 7.0 μm, we have directly observed the arrival of the injected electrons. Our measurements indicate an instrument-limited ~50-fs upper limit on the electron injection time under ambient conditions in air. We have compared the infrared transient absorption for noninjecting (blank) systems consisting of N3 in ethanol and N3 adsorbed to films of nanocrystalline Al ₂ O ₃ and ZrO ₂ , and found no indication of electron injection at probe wavelengths in the mid-IR (4.1 to 7.0 μm). At 1.52 μm interferences exist in the observed transient adsorption signal for the blanks.			
14. SUBJECT TERMS photovoltaics ; dynamics of dye injection ; N3 ; nanocrystalline ${\rm TiO_2}$			15. NUMBER OF PAGES 10
17. SECURITY CLASSIFICATION	18. SECURITY CLASSIFICATION	19. SECURITY CLASSIFICATION	16. PRICE CODE

Unclassified

NSN 7540-01-280-5500

Unclassified

Unclassified

Standard Form 298 (Rev. 2-89) Prescribed by ANSI Std. Z39-18 298-102